



**TRENTON
SYSTEMS**
Rugged Computers

MBS2000
Modular Blade
Chassis


2U - 19" DEPTH - UP TO 4 INDEPENDENT SBCs

Each processor blade is independent; 1200W total system power redundant

SWaP Optimized High-Performance Computing

Powered by two 1200W power supplies and as low as 48lbs for the fully-equipped system, the MBS2000 is the perfect combination of Size, Weight, and Power for applications that need a LOT of compute power.

PRODUCT DETAILS



Xeon or Core series CPUs

Enhance system performance with single Core™ or dual Intel® Xeon® Processors.



Reduced MTTR

Replace modular blades and power supplies in seconds. Customizable & flexible architecture for lower TCO.



1200W Redundant PSU

Redundant wattage in a low-profile power supply that easily supports all processor boards.



www.trentonsystems.com

Check out our website for configuration options.

Phone: (770) 287-3100

Email: sales@trentonsystems.com

MBS2000 MODULAR BLADE CHASSIS

TECH SPECS

Model Number

MBS2000

I/O

Rear:

Each modular blade supports

- 2 - General purpose 10/100/1000Base-T Ethernet ports,
- 1 - Dual-purpose Ethernet LAN port, that may function as a dedicated system management LAN or as a general purpose Ethernet interface
- 4 - USB 3.0 ports
- 1 - Serial port
- 1 - VGA port
- LEDs for system fault, Ethernet activity and BIOS post codes

Front:

Each modular blade supports

- 2 - USB 3.0 ports
- 1 - Power On/Off switch
- 1 - Status LED

Chassis Standard

EIA RS-310C 19" Rackmount Standard

Power Supply

1200W 1U, rear mounted, redundant - MTTR-Optimized Power Supply



Construction

Cold-rolled Steel with a black front surface and easy slide-in/slide-out 1U and 2U modular blade card assemblies and redundant power supply modules.

Dimensions

19.0" (W) 3.5" (H) x 19.125" (D)

48.26cm (W) 8.9cm (H) x 48.6cm (D)



www.trentonsystems.com

Check out our website for configuration options.

Phone: (770) 287-3100

Email: sales@trentonsystems.com