

# CSA-7210

*2U 19" Network Appliance with Intel® Xeon® Scalable Silver/Gold Processors  
for communications and computing infrastructure deployment*

## Features

- Up to 2 Gen1 or Gen2 Intel® Xeon® Scalable Processors
- 16x DDR4 2666 ECC REG memory up to 512GB
- Up to 8x NIM\* slots for network expansion
- Up to 4x 3.5" SATA 6 Gb/s, 1x CFast
- Up to 2x PCIe x16 Gen3
- TPM 1.2/ 2.0 module
- 2U 19" rackmount form factor
- Built-in Intel® QAT support

\*ADLINK Network Interface Module (NIM) is a proprietary form factor



## Specifications

### • CPU / Chipset / Memory

#### CPU

Up to 2x Gen1 or Gen2 Intel® Xeon® Scalable Processors up to 165W TDP, including:

Intel Xeon® Silver 4116 Processor 2.10 GHz (12C,85W)  
Intel Xeon® Silver 4210 Processor 2.20 GHz (10C,85W)  
Intel Xeon® Silver 4214 Processor 2.20 GHz (12C,85W)  
Intel Xeon® Silver 4216 Processor 2.10 GHz (16C,100W)  
Intel Xeon® Gold 6130 Processor 2.10 GHz (16C,125W)  
Intel Xeon® Gold 6230 Processor 2.10 GHz (20C,125W)  
Intel Xeon® Gold 6238T Processor 1.90 GHz (22C,125W)  
Intel Xeon® Platinum 8260 Processor 2.40 GHz (24C,165W)

#### Chipset

Intel® C622/C627 Chipset (SKU dependent)

#### Memory

16x DDR4-2666 DIMM sockets, ECC, registered, up to 512GB

### • BIOS

#### Chip

AMI BIOS on SPI flash memory

### • Operating System

Windows 7 64-bit,  
Windows 10 64-bit,  
Windows Server 2016,  
Linux Kernel 2.6 and above

### • I/O Interfaces

#### Expansion

8x Network Interface Module (NIM) slots

or

4x NIM slots\* and 2x PCIe x16 Gen 3 single-slot FHHL (Sku dependent)

2x RJ-45 10/100/1000BASE-T Ethernet ports

2x 10G SFP+ Ethernet ports

#### Console

1x RJ-45 serial port

#### USB

2x USB 3.0

#### Graphics

1x VGA port (internal)

### • Control

#### Power

Power button on the rear of the chassis

#### Management

IPMI v2.0 with iKVM and SOL support

# CSA-7210

## Specifications

### Storage

#### Drive Bays

- 1x onboard CFAST socket
- 1x 3.5" hot-swappable SATA 6 Gb/s drive bay
- 3x 3.5" internal SATA 6 Gb/s drive bays with hardware RAID support (SKU dependent)

### LEDs

Power, Alert, Drive Activity (user programmable)

### TPM

TPM1.2/2.0 (SKU dependent)

### Intel® QuickAssist Technology

100Gb/s Intel® QAT support (SKU dependent)

### Mechanical and Environmental

Form Factor: 2U 19" rackmount 438mm x 88mm x 560mm (WxHxD)

Fans: 3 fans, adaptive speed

Power: 800W or 1200W, AC/DC/HVDC

#### Temperature and humidity

Operating: 0°C to +40°C, 10%-85% RH @40°C, non-condensing

Storage: -40°C to +70°C, 5%-90% RH, non-condensing

#### Shock

Operating: Half-sine 2G, 11ms pulse, 100 pulses in each direction

Non-operating: Trapezoidal, 25G, 170 inches/sec delta V, three drops in each direction

#### Vibration

Non-operating Vibration: 2.2Grms, 10 minutes per axis in each direction

#### Acoustic

Sound pressure < 75 dBA @1m with all fans maximum speed

### Regulatory

FCC Class A, CE emissions, UL, CB, CCC and RoHS compliant

### MTBF

90,000 hours

### Software Support

Validated with DPDK, provides a high throughput for data plane packet processing

## Network Interface Modules (NIM)

### CSA-Z4X01

NIM1: 4-port GbE copper with LAN bypass

### CSA-Z5C4F

NIM2: 4-port GbE SFP w/o LAN bypass

### CSA-Z8X10

NIM3: 8-port GbE copper with LAN bypass

### CSA-Z5C2F

NIM4: 2-port 10GbE SFP+ w/o LAN bypass

### CSA-Z5C8F

NIM5: 8-port GbE SFP w/o LAN bypass

### CSA-Z5C8F+

NIM6: 8-port 10GbE SFP+ w/o LAN bypass

### CSA-Z5C4F+

NIM7: 4-port 10GbE SFP+ w/o LAN bypass

### CSA-Z5CQF+

NIM8: 1-port 40GbE QSFP+ Card w/o Lan bypass NIM card

## Mechanical Overview



Rear View



Front View