



## KEY FEATURES

- Single or double width AMC Filler panel
- RoHS compliant

The AMC999 is a filler panel for the single-width or double-width slots.

**AdvancedMC™**

## SPECIFICATIONS

Architecture		
Physical	Dimensions	Single-Width or double width
		Width: 2.89 in. (73.5 mm) (single width)
		Depth: 7.11 in. (180.6 mm) (single width)
Product Type	Filler Panel	To not allow air to flow through the front of the chassis
Standards		
AMC	Type	AMC.0
Configuration		
Power	AMC999	0W
Environmental	Temperature	Operating Temperature: -50° to 85° C
		Storage Temperature: -70° to +95° C
Other		
MTBF	MIL 217-F > 10,000,000 Hrs.	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS and NEBS	
Warranty	Two (2) years.	
Trademarks	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.	

## ORDERING OPTIONS

AMC999 - AOC - 000 - 000

**A = AMC-Width**

- 0 = Single-width
- 1 = Double-width

**C = Front Panel**

- 1 = Compact-Height
- 2 = Mid-Height
- 3 = Full-Height



Document No.4FM430-05 REV. 01 Date: March 2010 Pass one

